

# **Z-Furring Data**

## **Z-Furring**


Z-Furring is used to provide support for insulation while allowing for drywall attachment at masonry or concrete walls.Z-furring is available in 18, 30, and 43 mil thicknesses (25-18ga.) and 1", 1-1/2", 2" and 2-1/2" depths. Additional gauges are available upon request.

Size	Thickness (mils)	Gauge	Length	
1"	18	25	8'6", 10', 12' or Custom Lengths	
	30	20		
	43	18		
1-1/2"	18	25		
	30	20		
	43	18		
2"	18	25		
	30	20		
	43	18		
2-1/2"	18	25		
	30	20		
	43	18		
Custom sizes available per customer request				

#### **Steel Thickness**

B O'L	Course	Thickness (in)		
Mils	Gauge	Design	Minimum <sup>1</sup>	
18	25	0.0188	0.0179	
30	20	0.0312	0.0296	
43	18	0.0451	0.0428	

<sup>&</sup>lt;sup>1</sup> Minimum Thickness represents 95% of the design thickness and is the minimum acceptable thickness delivered to the job site based on AISI S100-16/S2-20.



#### **General Notes**

- 1. Structural framing members have a protective coating conforming to ASTM C 955.
- 2. Drywall framing members have a protective coating conforming to ASTM spec A 653/A 653M, G-40 min, or equivalent corrosion resistance.
- 3. Reference ASTM specification A 1003/A 1003 M table 1 for the universe of allowable coatings for light gauge steel framing.
- 4. All delivered material must be kept dry, preferably by being stored inside a building under a roof. If it is necessary to store material outside, it must be stacked off the ground, properly supported on a level platform, and fully protected from the weather. Reference ASTM C 754 section 8 and ASTM C 1007 section 4.
- 5. Drywall framing [nonstructural 25 gauge and 20 gauge] is not permitted in load bearing (i.e.axial load greater than 200 lbs.) or exterior applications (i.e.transverse load greater than 10 PSF). Reference ASTM C 645 section 3.2.2.

### **LEED Green Building Credits**

- MR Credit 2: Construction Waste Management MBA steel framing is 100% recyclable.
- MR Credit 4: Recycled Content MBA steel framing is formed from no less than 25.5% post-consumer and 6.8% pre-consumer recycled content.
- MR Credit 5: Regional Materials MBA has manufacturing facilities in multiple states.